

White, Laminated, **Medium Weight** Roll.

Product Data Sheet



Key Features & Benefits:

- Oil-Only Absorbency use on oil, Ideal for jobs where you need to absorb oil or coolants quickly, our laminated sorbents are constructed from a 3 layers of high-quality uniform polypropylene fibers.
- Absorbs Oils and repels water.
- Constructed by sonically bonded outer layers of durable polypropylene spundbond to a high-loft meltblown center to reduced linting. Tough and durable yet offering extreme softness and drape-ability needed for some situations.
- This medium weight pad will suit a variety of spill control and industrial clean-up situations that require oil absorption and not water.
- Unlike cellulose that burn immediately when exposed to flame or high heats. Our 100% Polypropylene absorbents are fire resistant and melts when exposed to high heats.
- Pads and rolls are perforated for easy and exact use.

Notes:

- Follow local, state, and federal regulations for proper disposal.
- Testing done using ASTM 726-12 (long testing) with medium viscosity oil and tap water.
- Weight and measurements are +/- 5%.

Regulations and Compliances

29 CRF 1910.22(a) (2)

"The floors of every workroom shall be maintained in a clean and, as far as possible, a dry condition" 29 CRF 1910.120(i) (1) (vii)

"suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur"

Item	Nominal Dimensions W x L	Туре	Units	Absorbency Capacity gal/L	Average Weight lb./kg	Units/Pallet	NMFC #	Class #
L-WM-SR150	15" X 150' (38cm X 46M)	Oil Only	2/bale	Up to 46/ 174	18/8	27	N/A	175

PDS Date: 07/13/18-Revised 11-14-2019















